

Electrical Tape

PVC Tape

PVC electrical tape provides fast and easy color coding, cable splicing, terminating, and wire insulating. These conformable high quality tapes have exceptional surface and adhesive characteristics. Tape is applied by overlapping each layer 50% and using tension. After the tape is adhered, the memory of the tape returns, tightening the seal and making the taped area even more waterproof.

Features and Benefits

- PVC Tape is ideal for general purpose electrical applications.
- Economical way to splice, terminate and insulate wire and cables.
- Meets Mil-Std. MIL-1-7798-A.



| | |
|------------------------------|-----------------------------------|
| MATERIAL | Flexible Polyvinyl Chloride (PVC) |
| Adhesion | 16 oz./inch |
| Tensile Strength | 15.4 lbs |
| Operating Temperature | +20°F to 176°F (-7°C to +80°C) |

| PART NO. | TYPE | Width (W) in. (mm) | Roll Length ft. (m) | Thickness (T) | Material | Color | Pkg. Qty. |
|-----------|--------|-----------------------|------------------------|---------------|----------|--------|-----------|
| ET330* | ET33 | 0.75 (19.05) | 33.0 (10.0) | 7.0 mil | PVC | Black | 10 |
| ET660* | ET66 | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | Black | 10 |
| ETST666* | ETST66 | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | Blue | 10 |
| ETST668* | | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | Gray | 10 |
| ETST665* | | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | Green | 10 |
| ETST663* | | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | Orange | 10 |
| ETST662* | | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | Red | 10 |
| ETST6610* | | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | White | 10 |
| ETST664* | | 0.75 (19.05) | 66.0 (20.1) | 7.0 mil | PVC | Yellow | 10 |

Dimensions in mm, inches in brackets. Subject to technical changes.

*This product meets UL standards. Please see appendix for specific file numbers.



Please note! Not all products listed on this page may have this approval. Please check our website for latest approvals.